2000 ORDERING SUPPLEMENT
MIDDLE EAST

0smidgcc

REQUIRED ON ALL MIDDLE EAST ORDERS		
RPO	**DESCRIPTION**	
BA0	Ornamentation Exterior Door Nameplate	X
EXP	Processing Option: GMODC, Export	X
K53	Fuel Sender Assy: Robust Fuel System	X
NM2	Leaded Fuel Provisions	X
R6K	Processing Option: Middle East	X
T62	Daytime Running Lights Delete	X
UC2	Speedometer: Kilo/Miles, Kilo Odometer, Positive Bias	X
UD4	Speed Warning Device	X
V60	Vehicle Statement - Incomplete Vehicle **Required** with YF7	X
V87	Vehicle Certification Label - **Not Available** with YF7	X
VC5	Shipping Label	X
VK3	Front License Plate Bracket	X
VPH	Export Vehicle Preparation – Includes (BAG)Export Parts Pkg., (VR6)Tie Down Hook, (V70)Tow Hook	X
Z5X	Mirror: Outside, Rearview, Arabic Language Warning. **Requires** DE2/DE5 Mirrors	X

NOTES: MUST ORDER A WINDOW PACKAGE, ZW2, ZW3, ZW4 OR ZW6.
MUST ORDER UL2 OR UL5.

MODEL AND POWERTRAIN AVAILABILITY					
MODEL	**DESCRIPTION**		**ENG.**	**DISPL.**	**TRANS.**
CG11405	Cargo Van, 135" Wheelbase	(C5Y) GVW 7100 lbs	L31	5.7L V8	M30
CG21405	Cargo Van, 135" Wheelbase	(C6P) GVW 8600 lbs	L31	5.7L V8	MT1
CG21705	Cargo Van, 155" Wheelbase	(C6P) GVW 8600 lbs	L31	5.7L V8	MT1
R CG31705	Cargo Van, 155" Wheelbase	(E23) GVW 9500 lbs	L65	6.5l V8	MT1

OTHER AVAILABLE EXPORT OPTIONS		
R		
DH6	Mirrors: Inside, Front Vanity, LH/RH Sunshade, Illuminated	A
NP5	Leather Wrapped Steering Wheel	A
R		
UL0	Radio: AM/FM Stereo, Seek/Scan, Cassette, Clock, ETR – **Requires UL2**	A
UL2	European Radio Frequency – **Requires UL0 and ZQ2; Includes U75**	A
UL5	Radio Delete	A
R YF2	Sales Package Ambulance Upfitter: Includes (B31) Covering Floor Vinyl, Front, Full Width, (G80) Axle Positraction Limited Slip, (ZW3) Window Package Rear Door, Side Rear Door.	A
R YF7	Upfitter Package: Includes (A19) Windows: Side Door Swing-Out, (BG5) Floor Covering Delete, (C60) Front Air Conditioning, (DE5) Mirrors: Outside, Rearview, LH/RH, Remote Control, Electric, R Heated, Folding, (KW2) Generator 124 AMP, (PNC) Panel Trim: Front Doors, Side Rear Door, Rear Doors, (V22) Chrome Grille, (V37) Chrome Front/Rear Bumpers, (YB9) Interior Paint Delete, (ZP0) Temporary Driver Seat, (ZQ2) Power Windows, Power Door Locks, (ZQ3) Cruise Control and Tilt Steering Column R In Addition CG11405 **Requires** ZW3 and N90/P06 Or **Requires** ZW6, N90 and YK6 CG21405/CG21705 **Requires** P06 and ZW3	A
YK6	Processing Option, SEO. **Requires** 6L2 Or **Requires** ZW6 & N90	A
6L2	Headliner: Full Length. **Not Available** TR9, YF7. **Requires** YK6	A

EXPORT RESTRICTIONS:	
AJ1	Deep Tint Glass - **Not Available**
KL5	Alternative Fuel Compatible Engine – **Not Available**
Z82	Trailering, Special Equipment – **Not Available**

G-VAN CARGO

2 WHEEL DRIVE	G11405
2 WHEEL DRIVE	G21405
2 WHEEL DRIVE	G21705
2 WHEEL DRIVE	G31405
2 WHEEL DRIVE	G31705

"STEP by STEP"

STEP #1:	SELECT	MODEL CODE Review Standard Equipment
STEP #2:	SELECT	PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE
STEP #3:	SELECT	POWER TEAM REQUIREMENTS
STEP #4:	SELECT	ADDITIONAL OPTIONS
STEP #5:	SELECT	COLOUR, TRIM AND PAINT APPLICATION CODE

2000 LIGHT DUTY TRUCKS

STEP #1: SELECT MODEL CODE – Review Standard Equipment

SAFETY/SECURITY	ZW9
Air bags: Driver and Passenger	S
Brakes: Four wheel antilock system. Power, self adjusting.	S
Child Safety Door Locks: On rear and side loading doors	S
Daytime Running Lights	S
Passlock™ Security System	S
Side Guard Door Beams: Front doors and side cargo door	S
Single Two-Sided Key	S
EXTERIOR	
Bumpers: Front and rear; painted argent. Rear bumper with entry assist step.	S
Corrosion Protection: Two-sided galvanized steel, except roof; 7-stage phosphate bath for entire vehicle; anti-chip coating on lower body area	S
Doors: Left hand and right hand front side doors; swing-out, hinged, side cargo doors	S
Rear load doors, full opening; hidden hinges; bumper extends beyond opened doors	S
Glass: All windows Solar-Ray™ tinted	S
Grille: Moulded plastic grille; integral "Chevrolet" emblem at centre	S
Headlamps, Halogen: Single rectangular, sealed beam; hi/low beam	S
Horns, Dual	S
Lights: Backup Lamps; Combination Parking/Direction/Hazard; Combination Tail/Stop/Direction/Hazard; Headlamps; License Plate Lamp; Side Marker Lamps with Reflectors; Centre High Mounted Stop Lamp.	S
Mirrors: Left hand and right hand manual control, black, fold-away	S
Spare Tire Carrier: Winch-type; under body at rear, behind axle	S
Wheels: Steel wheel, argent with black center cap.	S
Windshield Wipers and Washers: Intermittent wiper system, wet-arm washer system	S
INTERIOR	
Armrests: Left hand and right hand side doors; padded	S
Assist Handle: Front passenger side	S
Cup Holders: Two, in instrument panel	S
Floor Covering: Embossed black vinyl, front and rear, full width	S
Headliner: Cloth above driver and passenger seats	S
Headlamps On Warning Alarm	S
Heater and Defogger: Outside air heater with windshield and side window defoggers	S
Instruments: Gauges - Speedometer, Odometer, Fuel, Voltmeter, Temperature, Oil Pressure and Trip Odometer	S
Lighter, Cigarette	S
Lights: Front, centre and rear dome lamps with front door-actuated switches	S
Parcel Tray: On top surface of instrument panel extension (with L29 or L65 only)	S
Power Outlet, Auxiliary: one covered auxiliary power outlet on instrument panel	S
Radio Equipment: Electronically Tuned AM/FM Stereo Radio with Seek-Scan and Digital Clock	S
Seats: Reclining high back front bucket driver and passenger seats, with integral head restraints and map pockets	S
Steering Wheel and Column: Black energy-absorbing steering column, black vinyl wheel	S
Stowage Box: In instrument panel extension, lighted	S
Sunshades: Colour-keyed; right hand sunshade has full map strap	S
Tools: Scissor-type jack and wheel wrench. Located at right rear of vehicle	S

S Standard

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

REFER TO GENERAL INFORMATION SECTION FOR HOW TO ORDER INFORMATION WHEN CHANGING POWERTRAIN

NOTE: SEE POWER TEAM CHARTS FOR CORRECT UPGRADES COMPATIBILITY

OPTION DESCRIPTION	OPTION CODE	SELECT-A-UNIT CODES 1	2
PREFERRED EQUIPMENT GROUP	--	1SA	1SB
BODY CODE: Standard	ZW9	X	X
Engine: Vortec 4300 SFI V6 (G11405, G21405, G21705)	L35	U	U
Engine: Vortec 5700 SFI V8 (G31405, G31705)	L31	U	U
Transmission: 4 Speed Automatic w/Overdrive (G11405)	M30	X	X
Transmission: 4 Speed Automatic w/Overdrive (G21405, G21705)	M30	U	U
Transmission: 4 Speed Automatic W/Overdrive (G31405, G31705)	MT1	X	X
GVWR: 2767 kgs (6100 lbs) (G11405)	C5M	U	U
GVWR: 3311 kgs (7300 lbs) (G21405, G21705)	C6A	U	U
GVWR: 4309 kgs (9500 lbs) (G31405, G31705)	E23	X	X
Axle, Rear: 3.42 Ratio (G11405, G21405, G21705)	GU6	U	U
Axle, Rear: 3.73 Ratio (G31405, G31705)	GT4	U	U
Tires: P215/75R-15/N ALS SBR Blackwall (G11405)	YCU	U	U
Tires: LT225/75R-16/D ALS SBR Blackwall (G21405, G21705)	YHP	U	U
Tires: LT245/75R-16/E ALS SBR Blackwall (G31405, G31705)	YHH	X	X
Seats: High Back Buckets, Driver and Passenger	ZX2	U	U
Air Conditioning: Front	C60		U
Convenience Group: Tilt Wheel and Speed Control	ZQ3		X

X **Option Included in Select-A-Unit DO NOT DELETE**
U **Option Included in Select-A-Unit and May Be Deleted if Substitute Option is Specified**

2000 LIGHT DUTY TRUCKS

STEP #2: SELECT PREFERRED EQUIPMENT GROUP AND IDENTIFY SELECT-A-UNIT CODE

Description	Model Code	Body Code	Select-A-Unit Code	Option Code

2 WHEEL DRIVE – 1500 SERIES

STANDARD – 135 INCH WHEELBASE

Model Price	**G11405**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G11405	ZW9	2	1SB

2 WHEEL DRIVE – 2500 SERIES

STANDARD – 135 INCH WHEELBASE

Model Price	**G21405**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G21405	ZW9	2	1SB

STANDARD – 155 INCH WHEELBASE

Model Price	**G21705**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G21705	ZW9	2	1SB

2 WHEEL DRIVE – 3500 SERIES

STANDARD – 135 INCH WHEELBASE

Model Price	**G31405**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G31405	ZW9	2	1SB

STANDARD – 155 INCH WHEELBASE

Model Price	**G31705**	**ZW9**	**1**	**1SA**
Preferred Equipment Group Price	G31705	ZW9	2	1SB

STEP #3: SELECT POWER TEAM REQUIREMENTS

Engine, Transmission, Axle Ratio and GVWR Code Must Be Specified

G11405

GVWR Code	§ C5M	¶ C5Y	
kgs	2767	3220	
lbs	6100	7100	
Axle Ratio	3.42	3.42	3.73

Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type	Axle Ratio Codes		
L35 V6	4.3 Litre	SFI	200 @ 4400	M30-Automatic w/Overdrive	GU6	GU6	GT4
L30 V8	5.0 Litre	SFI	220 @ 4600	M30-Automatic w/Overdrive	GU6	GU6	---
L31 V8	5.7 Litre	SFI	245 @ 4600	M30-Automatic w/Overdrive	---	GU6	---

§ **Requires YCU Tires**
¶ **Requires YHA, YHB or YHM Tires**

G21405, G21705

GVWR Code	§ C6A	¶ C6P	
kgs	3311	3901	
lbs	7300	8600	
Axle Ratio	3.42	3.73	4.10

Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type	Axle Ratio Codes		
L35 V6	4.3 Litre	SFI	200 @ 4400	M30-Automatic w/Overdrive	GU6	---	---
				MT1-Automatic w/Overdrive	---	---	GT5
L30 V8	5.0 Litre	SFI	220 @ 4600	M30-Automatic w/Overdrive	GU6	---	---
L31 V8	5.7 Litre	SFI	245 @ 4600	M30-Automatic w/Overdrive	GU6	---	---
				MT1-Automatic w/Overdrive	---	* GT4	* GT5
L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive	---	#GT4	GT5

§ **Requires YHP Tires**
¶ **Requires YHF Tires**
* **Horsepower is 250 @ 4600 RPM**
\# **Not Available model G21405.**

G31405, G31705

GVWR Code	E23		
kgs	4309		
lbs	9500		
Axle Ratio	3.42	3.73	4.10

Engine Type	Displace-ment	Fuel System	Net HP	Transmission Type	Axle Ratio		
L31 V8	5.7 Litre	SFI	250 @ 4600	MT1-Automatic w/Overdrive	---	GT4	GT5
L29 V8	7.4 Litre	SFI	290 @ 4000	MT1-Automatic w/Overdrive	* GU6	GT4	GT5
L65 V8	6.5 Litre 395 Cu. In.	Turbo Diesel	195 @ 3400	MT1-Automatic w/Overdrive	---	#GT4	GT5

* **Not Available with G80**
\# **Not Available model G31405.**

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code
ENGINES: – Refer to Power Teams Chart for compatibility.	
Vortec 4300 Sequential Fuel Injection (SFI) V6.	
With MT1 includes extra capacity engine oil cooling	L35
Vortec 5000 Sequential Fuel Injection (SFI) V8	L30
Vortec 5700 Sequential Fuel Injection (SFI) V8.	
With MT1 includes an auxiliary transmission oil cooler and extra capacity engine oil cooling.	
Optional with: G11405, G21405, G21705	L31
G31405, G31705	L31
Vortec 7400 Sequential Fuel Injection (SFI) V8.	
Includes extra capacity engine oil cooling and an auxiliary transmission oil cooler	L29
6.5 Litre (395 Cu. In.) Turbo Diesel V8.	
Includes an auxiliary engine oil cooler and an auxiliary transmission oil cooler. Includes KW2, dual batteries – one is on frame rail behind driver's door, the other is in right hand corner under hood.	
Optional with: G21405, G21705	L65
G31405, G31705	L65
Alternative Fuel Compatible Engine:	
Provides only the engine with internal modifications for operation with natural or propane gas. **Requires** L31 and MT1. **Requires** C6P with G21405, G21705. **Not Available** G11405.	KL5
TRANSMISSION: – Refer to Power Teams Chart for compatibility	
4-Speed Electronic Automatic with Overdrive	M30
4-Speed Electronic Automatic with Overdrive	MT1
GVWR: – Refer to Power Teams Chart for compatibility	
G11405	
2767 kgs (6100 lbs)	C5M
3220 kgs (7100 lbs)	C5Y
G21405, G21705	
3311 kgs (7300 lbs)	C6A
3901 kgs (8600 lbs) Includes KW2.	C6P
G31405, G31705	
4309 kgs (9500 lbs) Includes KW2. Includes an auxiliary transmission oil cooler.	E23
AXLES, REAR: – Refer to Power Teams Chart for compatibility	
Ratio Codes 3.42	GU6
3.73	GT4
4.10	GT5
Locking Differential. **Not Available** with GU6 on G31405 or G31705	G80
TIRES:	
P215/75R-15/N All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Requires C5M. Optional with: G11405	YCU
P235/75R-15/X All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Requires C5Y. Optional with: G11405	YHA
P235/75R-15/X All Season Steel Belted Radial White Stripe. Front, Rear and Spare.	
R **Requires** C5Y and YF7. Optional with: G11405	YHB
P235/75R-15/XL All Season Steel Belted Radial White Outline Lettered. Front, Rear and Spare.	
R **Requires** C5Y and YF7. Optional with: G11405	YHM
LT225/75R-16/D All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Requires C6A. Optional with: G21405, G21705	YHP
LT225/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Requires C6P. Optional with: G21405, G21705	YHF
LT245/75R-16/E All Season Steel Belted Radial Blackwall. Front, Rear and Spare.	
Optional with: G31405, G31705	YHH
Spare Tire Delete. Deletes Spare Tire, Wheel and Jack.	
Optional with: with YCU on G11405	ZX9
with YHA on G11405	ZX9
R with YHP on G21405, G21705	ZX9
R with YHF on G21405, G21705	ZX9
with YHH on G31405, G31705	ZX9

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

SEATS AND SEAT TRIM:
High Back Buckets, Driver and Passenger. With 'G' Trim includes inboard armrests and Scotchgard™.
Optional with: ..... 'W' or 'G' Trim ZX2
High Back Bucket, Driver side only. **Deletes** standard passenger side airbag.
Passenger seat cannot be added later. With 'G' Trim includes inboard armrests and Scotchgard™.
Optional with: ..... 'W' or 'G' Trim ZX1

AIR BAG, DRIVER SIDE ONLY:
Deletes the passenger side Air Bag.
Requires ZX2. **Requires** C6P on G21405 and G21705.
Not Available on G11405. ..... AJ3

AIR CONDITIONING:
Front. Includes instrument panel integrated outside air system and increased capacity cooling.
Recommended for front seat area cooling only. Included with C69. Required with YF2.
Optional with: ..... SAU 1 ..... C60

Front and Rear. Includes C60, KW2, C36 and rear overhead mounted recirculating air system.
Not Available YF2 or YF7.
Optional with: ..... SAU 1 on G11405, G21405, G21705 ..... C69
..... SAU 2 on G11405, G21405, G21705 ..... C69
..... SAU 1 on G31405, G31705 ..... C69
..... SAU 2 on G31405, G31705 ..... C69

ALTERNATOR, 124 AMP:
Included with C69, C6P, L65. Included with G31405, G31705.
Optional with: ..... G11405, G21405, G21705 ..... KW2

AMBULANCE PREP PROVISIONS:
Includes B31, G80, ZW3, dual 100 AMP alternators, front and rear chrome bumper and provisions for rear air conditioning and rear heater.
Requires L65, MT1, GT5. **Requires** C60 with SAU 1.
Not Available C36, C69, DE5, TR9, YA2.
Deletes dome lamp and rear cargo lamp and headliner.
Optional with: ..... with ZR7 and SAU 1 on G31705 ..... YF2
..... without ZR7 and SAU 1 on G31705 ..... YF2
..... SAU 2 on G31705 ..... YF2

APPEARANCE, DELUXE:
Includes chrome grille and chrome front and rear bumpers.
R Optional with: ..... SAU 1 or 2 ..... ZR7

COLD CLIMATE PROVISION:
Includes engine block heater. **Not Available** L65 ..... V10

CONVENIENCE GROUPS:
Power Windows and Power Door Locks ZQ2
Tilt Wheel and Speed Control ..... SAU 1 ..... ZQ3

DOOR:
Sliding side rear door. Includes Child Safety Door Lock.
Swing out side door is standard. **Not Available** YF2 ..... YA2

FLOOR COVERING DELETE:
Black vinyl, front floor seating area only, full width.
Deletes the standard rear black vinyl floor covering B31

HEATER:
Rear. Located on left side, ahead of rear wheelhouse.
Included with C69. **Not Available** YF2 or YF7. ..... C36

LIGHTING, AUXILIARY:
Includes reading lamps, front and side door stepwell lamps, underhood lamp.
Not Available YF2 or YF7 ..... TR9

2000 LIGHT DUTY TRUCKS

STEP #4: SELECT ADDITIONAL OPTIONS

Description	Option Code

MIRRORS, EXTERIOR:
Left hand and right hand electric remote control, with defog feature; folding.
Requires C60 or C69. **Requires** ZQ2. **Not Available** YF2. **Not Available** B3D DE5

PAINT SCHEME: See Colour, Trim and Seat Availability Chart. Solid ZY1

RADIO EQUIPMENT:
Antenna, Power. **Not Available** with UL5 ..... U75
Radio Delete. Deletes Antenna UL5
Electronically Tuned AM/FM Stereo Radio with Seek-Scan, Stereo Cassette Tape and Digital Clock. Includes fixed mast antenna, premium dual front and rear speakers UM6

SCHOOL BUS CHASSIS EQUIPMENT:
Deletes right hand front rubber mat and right hand front floor insulation.
Requires ZX1. **Requires** L31 or L65. **Not Available** with Z82. **Not Available** with DE5.
Includes visual and audible brake warning system, and Incomplete Vehicle Document.
Optional with: ..... G31405, G31705 ..... B3D

TRAILERING, SPECIAL EQUIPMENT:
Heavy Duty. Includes Weight Distributing Platform Type Trailer Hitch and 8-lead type wiring harness with heavy duty flasher. Additional cooling not required.
Not Available with B3D Z82

UPFITTER PACKAGE, RECREATIONAL VEHICLE:
Available ONLY for (CU7) Kuwait, (CU8) Saudi Arabia, (CW2) Gulf States, (CW6) Guam, (CW7) Caribbean, (CW9) Miscellaneous Unregulated (Africa)

Includes (BG5) Floor Covering Delete, (C60) Air Conditioner, Front, (V22) Chrome Radiator Grille, (V37) Chrome Bumpers, Front/Rear, (YB9) Interior Paint Delete, (ZP0) Temporary Seating Arrangement, (ZQ2) Convenience Package, Power Window/Door Locks, (ZQ3) Convenience Package, Cruise Control, Tilt Steering Wheel, (ZW3) Window Package; Rear, Side Rear Doors.
Not available C36, C69 or TR9. ..... YF7

UPFITTER PACKAGE, RECREATIONAL VEHICLE:
Available for all export EXCEPT (CU7) Kuwait, (CU8) Saudi Arabia, (CW2) Gulf States, (CW6) Guam, (CW7) Caribbean, (CW9) Miscellaneous Unregulated (Africa)

Includes (BG5) Floor Covering - Delete, (DH6) Mirror-Inside, Front, Vanity, LH/RH, Sunshade, Illuminated, (NP5) Leather Wrapped Steering Wheel, (PNC) Trim Panel, Front, Side Rear, Rear Doors, (P06) Wheel Trim Discs, (YB9) Interior Paint Process-Delete, (ZP0) Temporary Driver Seating Arrangement, (ZQ2) Convenience Group; Power Windows, Power Door Locks (ZQ3) Convenience Group; Cruise Control, Tilt Steering Wheel, (ZW3) Window Package; Rear, Side Rear Doors. YF9

WHEEL TRIM: Bright trim rings with chromed centre caps P06

WINDOWS, SWING-OUT:
Rear doors. **Requires** ZW2. Included with A19 ..... A18
Rear side cargo door. Includes A18. **Requires** ZW3, ZW4 or ZW6 ..... A19

WINDOW PACKAGES:
Windows are stationary unless ordered with A18 or A19 (except with ZW6 which includes swing-out left hand centre body glass).
Rear doors, fixed ZW2
Rear doors and rear side doors, fixed (sliding or swing out) ZW3
Rear doors, right hand side, fixed ZW4
Complete body (includes swing-out left hand centre body glass) ZW6

DESCRIPTION	Order Code	Lead Time Days

SPECIAL EQUIPMENT WHEN INSTALLED AT ASSEMBLY PLANT

HEADLINER, FULL LENGTH: **Not Available** with TR9, YF2 or YF7. ..... 6L2

PAINTS: Solid. **Requires** 01U Colour Code One.

Green, Woodland	9V5	--
Tan, Doeskin	9V9	--
Yellow, Wheatland	9W3	--
Orange, Tangier	9W4	--

ZY1 PAINT APPLICATION

	Seat Ordering Information			Interior Trim		
Body Code	Type	Seat Material	Option Code	Navy	Neutral	Medium Gray
ZW9	High Back Bucket	Vinyl	ZX2 §	26W	52W	92W
	High Back Bucket	Custom Cloth	ZX2 §	26G	52G	92G

Exterior Paint Colour	Code	Available Combinations		
Medium Storm Gray (Met)	14U	X	---	X
Fernmist Green (Met)	31U	---	X	X
Indigo Blue (Met)	39U	X	X	X
Black	41U	---	X	X
Summit White	50U	X	X	X
Dark Carmine Red (Met)	51U	---	X	X
Light Autumnwood (Met)	55U	---	X	---
Victory Red	74U	---	X	X
Dark Bronzemist (Met)	76U	---	X	X

§ **Seat option may be changed, check SEATS AND SEAT TRIM.**

DATE: February 14, 2000
REVISION NO: 00-3

GENERAL MOTORS OVERSEAS DISTRIBUTION CORPORATION

2000

UPDATE

CHEVROLET

G-VAN CARGO

TRUCK TECHNICAL PAGES

Attached is revision 00-3 of the Light Duty Truck Technical Pages.

The information contained in the Technical Pages is confidential and should not be disclosed to unauthorized persons or used for non-business purposes.

MODEL SELECTION SUMMARY

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD/OPT)	STANDARD ENGINE/ TRANS	OPTIONAL ENGINE/ TRANS	GVWR KG (LB)	GAWR KG (LB) FRONT/ REAR	MAXIMUM PAYLOAD KG (LB)	MAX GROSS TRAILER WT/ TONGUE LOAD KG (LB)
EXPRESS CARGO								
G10								
G10 REGULAR WHEELBASE	G11405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4	2767 (6100)	1437/1436 (3168/3167)	639 (1410)	2449/* (5400) 2631/* (5800)
G10 REGULAR WHEELBASE	G11405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3220 (7100)	1633/1780 (3600/3968)	1078 (2379)	2449/* (5400) 2631/* (5800) 3311/* (7300)
G20								
G20 REGULAR WHEELBASE	G21405/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3311 (7300)	1624/1987 (3580/4380)	1102 (2431)	2222/* (4900) 2540/* (5600) 2767/* (6100)
G20 REGULAR WHEELBASE	G21405/ ZW9	2/1	4300 V6/A4	— 5700 V8/A4 6.5L V8/A4	3901 (8600)	1724/2431 (3800/5360)	1570 (3462)	2449/* (5400) 3765/* (8300) 4037/* (8900)
G20 EXTENDED WHEELBASE	G21705/ ZW9	2/1	4300 V6/A4	— 5000 V8/A4 5700 V8/A4	3311 (7300)	1624/1987 (3580/4380)	1018 (2245)	2222/* (4900) 2540/* (5600) 2767/* (6100)
G20 EXTENDED WHEELBASE	G21705/ ZW9	2/1	4300 V6/A4	— 5700 V8/A4 6.5L V8/A4	3901 (8600)	1860/2431 (4100/5360) 1950/2431 (4300/5360)	1485 (3275)	2449/* (5400) 3765/* (8300) 4037/* (8900)
G30								
G30 REGULAR WHEELBASE	G31405/ ZW9	2/1	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1860 (4101)	3674/* (8100) 4536/* (10000) 3992/* (8800)
G30 EXTENDED WHEELBASE	G31705/ ZW9	2/1	5700 V8/A4	— 7400 V8/A4 6.5L V8/A4	4309 (9500)	1950/2760 (4300/6084)	1772 (3907)	3674/* (8100) 4536/* (10000) 3992/* (8800)

*Trailer tongue weight should be 10 to 15% of total loaded trailer weight. (up to 1000 lbs).

POWERTRAINS

ENGINES

	VORTEC 4300 V6	VORTEC 5000 V8	VORTEC 5700 V8	VORTEC 7400 V8 HD	6.5L V8 DIESEL HD
Order Code	L35 (Standard G11405/ 21405/21705)	L30	L31	L29	L65
Availability	G11405, G21405 and G21705	G11405 and G21405/ G21705 w/C6A	All	G31405/ G31705	G21405/ G21705 w/C6P and G31405/ G31705
SAE Net Kilowatts @ rpm (Horsepower @ rpm)	149 @ 4400 (200 @ 4400)	164 @ 4600 (220 @ 4600)	190 @ 4600 (255 @ 4600)	216 @ 4000 (290 @ 4000)	145 @ 3400 (195 @ 3400)
SAE Net Torque N-m @ rpm (lb-ft @ rpm)	339 @ 2800 (250 @ 2800)	380 @ 2800 (280 @ 2800)	447 @ 2800 (330 @ 2800)	556 @ 3200 (410 @ 3200)	583 @ 1800 (430 @ 1800)
Fuel System	SFI	SFI	SFI	SFI	Indirect Fuel Injection
Standard Delco Freedom Battery (12 volt, negative ground) Cold Cranking Amps @ -17.8° C (0°F)	600	600	600	600	2 @ 600 each
Standard Delcotron Alternator Maximum Capacity Amps	100[1]	100	100	124	124

[1]124 amp alternator is required on or above 3901kg (8600lb) GVWR.
[2]100 amp alternator is standard on G21405/G21705 w/C6P.

TRANSMISSIONS

	ELECTRONIC AUTOMATIC 4-SPEED OVERDRIVE W/TORQUE CONVERTER CLUTCH (4L60-E) (Includes brake/transmission shift interlock)	ELECTRONICALLY CONTROLLED AUTOMATIC 4-SPEED W/OD HEAVY DUTY (4L80-E) (Includes brake/transmission shift interlock)
Order Code	M30 (Standard w/C5M/C5Y/C6A)	MT1 (Standard w/C6P/E23)
Application	L35/L30/L31	L35 HD/L31 HD/L29/L65
Gear Ratios		
First	3.06	2.48
Second	1.63	1.48
Third	1.00	1.00
Fourth	0.70	0.75
Reverse	2.29	2.08

REAR AXLES

Availability	G11405 w/C5M	G11405 w/C5Y		G21405/G21705 w/C6A	G21405/G21705 w/C6P w/o L65		G21405/G21705 w/C6P and L65 only; G31405/G31705		
Make	GM	GM		GM	GM		GM		
Capacity kg (lb)	1588 (3500) Semi-Floating	1814 (4000) Semi-Floating		2177 (4800) Semi-Floating	2585 (5700) Full-Floating		2760 (6084) Full-Floating		
Pinion and Ring Gear Type	Hypoid	Hypoid		Hypoid	Hypoid		Hypoid		
Engine Availability[1]	L35/L30	L35 L30 L31	L35	L35 L30 L31	L31	L35/ L31	L29	L29/ L31/ L65	L29/ L31/ L65
Axle Ratio Code	GU6 (Standard)	GU6	GT4	GU6 (Standard)	GT4	GT5	GU6	GT4[2]	GT5
Ratio	3.42	3.42	3.73	3.42	3.73	4.10	3.42	3.73	4.10
Pinion Teeth	12	12	11	12	11	10	12	11	10
Ring Gear Teeth	41	41	41	41	41	41	41	41	41
Ring Gear Diameter mm (in.)	218 (8.6)	218 (8.6)	218 (8.6)	241 (9.5)	241 (9.5)	241 (9.5)	267 (10.5)	267 (10.5)	267 (10.5)

Note: Axle ratio availability depends on model, powertrain and emissions selected.
[1]Engine applications are heavy duty (HD) at 3901 kg (8600 lb) GVWR or above.
[2]Standard axle on G31405 and G31705.

BRAKES

Type	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock	Power Self-Adjusting 4-Wheel Anti-Lock
Application	G11405; G21405 G21705 w/C6A	G21405/G21705 w/C6P and w/o L65	G21405/G21705 w/C6P and L65; G31405/G31705
Front Rotor Size mm (in.)	Disc 294 x 32 (11.57 x 1.25)	Disc 318 x 32 (12.5 x 1.26)	Disc 318 x 32 (12.5 x 1.26)
Rear Size mm (in.)	Drum 283 x 70 (11.15 x 2.75)	Drum 330 x 63.5 (13 x 2.5)	Drum 330 x 88.9 (13 x 3.5)
Booster Type	Vacuum	Hydraulic	Hydraulic
Parking Brake Type Operation	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal	Cable to Rear Wheels Pedal

STANDARD CHASSIS FEATURES

AIR BAGS	Driver and passenger
ENGINE BLOCK HEATER	
EXHAUST SYSTEM Type	Aluminized stainless steel single exhaust with converter
FRAME Type	Full-length, all-welded ladder-type construction
FUEL TANK Location	Forward of rear axle between frame rails
Capacity (approx.)	117 litres (25.8 imperial gal.)
GVWR	
C5M–G11405	2767 kg (6100 lb)
C6A–G21405/G21705	3311 kg (7300 lb)
E23–G31405/G31705	4309 kg (9500 lb)
STEERING Type	Integral Power

SUSPENSION, FRONT	Independent
Capacity	
G11405; G21405/ G21705 w/C6A	1633 kg (3600 lb)
G21405/G21705 w/C6P; G31405/ G31705	1950 kg (4300 lb)
Springs	Coil
Capacity	
G11405; G21405/ G21705 w/C6A	816 kg (1800 lb) each
G21405 w/C6P	862 kg (1900 lb) each
G21705 w/C6P w/o L65	930 kg (2050 lb) each
G21705 w/C6P and L65;G31405/ G31705	975 kg (2150 lb) each
Shock absorbers	32 mm (1.26") piston diameter
Stabilizer bar	30 mm (1.18") diameter
SUSPENSION, REAR	
Springs	Multi-leaf
Capacity	
G11405 w/C5M	718 kg (1583 lb) each
G11405 w/C5Y	900 kg (1984 lb) each
G21405/G21705 w/C6A	993 kg (2190 lb) each
G21405/G21705 w/C6P	1215 kg (2680 lb) each
G31405/G31705	1380 kg (3042 lb) each
Shock absorbers	32mm(1.26") diameter
WHEELS	
Type	Five disc, painted argent with 4 black plastic centre caps
Size	
G11405	381mm x 152mm (15" x 6")
G21405/21705/ G31405/31705	406mm x 165mm (16" x 6.5")
Attachment	
G11405	5 bolts on 127mm (5") circle
G21405/21705 with C6A	6 bolts on 139.7mm (5.5") circle
G21405/21705 with C6P; G31405/31705	8 bolts on 165mm (6.5") circle

TIRES

KEY: ALS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW = BLACKWALL WS = WHITE STRIPE WOL = WHITE OUTLINE LETTERED

TIRE DESCRIPTION		FRONT, REAR, SPARE
P215/75R15/N	ALS/SBR/BW	YCU (Standard w/G11405)
P235/75R15/X	ALS/SBR/BW	YHA
P235/75R15/X	ALS/SBR/WS	YHB
P235/75R15	ALS/SBR/WOL	YHM
LT225/75R16/D	ALS/SBR/BW	YHP (Standard w/G21405/21705)
LT225/75R16/E	ALS/SBR/BW	YHF
LT245/75R16/E	ALS/SBR/BW	YHH (Standard w/G31405/31705)

DIMENSIONS

SERIES	G10	G20		G30	
MODEL	**REGULAR WHEELBASE**	**REGULAR WHEELBASE**	**EXTENDED WHEELBASE**	**REGULAR WHEELBASE**	**EXTENDED WHEELBASE**
MODEL NUMBER	**G11405/ZW9**	**G21405/ZW9**	**G21705/ZW9**	**G31405/ZW9**	**G31705/ZW9**
EXTERIOR DIMENSIONS					
BODY					
Wheelbase mm (in.)	3429 (135.0)	3429 (135.0)	3937 (155.0)	3429 (135.0)	3937 (155.0)
Overall Length mm (in.)	5555 (218.7)	5555 (218.7)	6063 (238.7)	5555 (218.7)	6063 (238.7)
Overall Height Nominal mm (in.)	C5M-2022 (79.6)	C6A-2096 (82.5)	C6A-2060 (81.1)	E23-2131 (83.9)	E23-2096 (82.5)
Maximum Width mm (in.)	2017 (79.4)	2012 (79.2)	2012 (79.2)	2017 (79.4)	2012 (79.2)
Bumper to Axle					
Front mm (in.)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)	859 (33.8)
Rear mm (in.)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)	1267 (49.9)
Ground to Top of Rear Load Floor mm (in.)	617 (24.3)	696 (27.4)	704 (27.7)	737 (29.0)	737 (29.0)
Ground Clearance Front/Rear mm (in.)	175(6.9)/170 (6.7)	206 (8.1)/183 (7.2)	206 (8.1)/203 (8.0)	221 (8.7)/216 (8.5)	221 (8.7)/216 (8.5)
Side Load Door Sliding (YA2)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width mm (in.)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)	1036 (40.8)
Side Load Door Swing-Out (E24)					
Opening Height mm (in.)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)	1247 (49.1)
Opening Width mm (in.) —Both Doors Open	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)	1186 (46.7)
Rear Load Door					
Opening Height mm (in.)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)	1242 (48.9)
Opening Width mm (in.)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)	1445 (56.9)
Turning Diameter Curb-to-Curb m (ft)	13.7 (45.1)	13.8 (45.2)	16.3 (53.4)	14.5 (47.5)	16.3 (53.5)
SIGN PANEL AREA mm (in.)	2959 x 1440 (116.5 x 56.7)	2959 x 1440 (116.5 x 56.7)	3467 x 1440 (136.5 x 56.7)	2959 x 1440 (116.5 x 56.7)	3467 x 1440 (136.5 x 56.7)
STEP-UP HEIGHT mm (in.)					
Front Door	419 (16.5)	483 (19.0)	483 (19.0)	521 (20.5)	523 (20.6)
Second Door	394 (15.5)	457 (18.0)	457 (18.0)	495 (19.5)	498 (19.6)

DIMENSIONS (CONT.)

SERIES	G10	G20		G30	
MODEL	REGULAR WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE	REGULAR WHEELBASE	EXTENDED WHEELBASE
MODEL NUMBER	G11405/ZW9	G21405/ZW9	G21705/ZW9	G31405/ZW9	G31705/ZW9
INTERIOR DIMENSIONS					
Headroom Front mm (in.)	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)	1031 (40.6)
Legroom Front mm (in.)	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)	1044 (41.1)
Shoulder Room Front mm (in.)	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)	1748 (68.8)
Hip Room Front mm (in.)	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8)	1621 (63.8
Load Floor Length w/Front Seats mm (in.)	3233 (127.3)	3233 (127.3)	3741 (147.3)	3233 (127.3)	3741 (147.3)
Inside Width @ Beltline mm (in.)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)	1917 (75.5)
Inside Width between Wheelhousings w/mat mm (in.)	1336 (52.6)	1336 (52.6)	1334 (52.5)	1336 (52.6)	1334 (52.5)
Interior Height mm (in.)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)	1367 (53.8)
Cargo Volume w/Front Seat litres (cu ft)	7569 (267.3)	7569 (267.3)	8971 (316.8)	7569 (267.3)	8971 (316.8)